








VALVE SERIES	
	<p>Simply Italy Type: Stereo Integrated Valve Amplifier Valve complement: 2 x ECC82 (12AU7) 2 x EL34 (6CA7) Output stage: Single-ended, ultralinear, Class-A Output power: Approx. 12 watts per channel Output impedance: 6 Ohm Input: 4 Line , 1 USB DAC optional Negative feedback: 5 dB or 1.8 dB Dimensions: 26 cm x 35 cm x 19cm Net weight: 15kg</p> <p>Cherry / Black € 2.490</p> <p>Simply Italy Incl. USB-dac (PCM 384kHz DSD-128) € 2.740</p>
	<p>Triode 25 Output Stage: Push-pull, ultralinear, Class-AB Output Power: Approx. 45 watt per channel in Ultralinear (Pentode) configuration. Approx. 25 watt per channel Triode configuration Output Impedance: 6 Ohm Input: 4 Linea (1 Tape), 1 USB DAC Output: 1 Tape out, 1 Sub Out Negative feedback: 5 dB or 1.8 dB Valve complement: 2 x ECC83, 1 x ECC82, 4 x EL34 Dimensions: 30 cm x 45 cm x 20cm Net weight : 20 Kg</p> <p>Cherry / Black</p> <p>Triode 25 Incl. USB-dac (PCM 384kHz DSD-128) € 3.590</p>
	<p>S6 mkII Type: Stereo Integrated Valve Amplifier Valves: 2 x ECC83, 6 x EL34 (Bias adjustable for each power valves) Output Stage: single-ended parallel, ultraliner Classe: pure A class Output Power: 30/35 Watt/channel Frequency Response: 20 – 50000 Hz Output Impedance: 6 Ohm Inputs: 5 line Outputs: 1 tape Dimensioni : 35 cm x 21cm x 49 cm (L x H x D) Net Weight: 25 kg</p> <p>Cherry / Black € 4.900</p>
	<p>Preludio Type: Stereo Integrated Valve Amplifier Output Stage: single ended ultraliner A class Output Power: 14W / channel Inputs: 4 line, 1 tape Outputs: 1 tape, 1 sub woofer Output Impedance: 6 ohm Frequency Response: 20Hz – 85kHz (-1dB@ 7 W) Valves: 2 x 6550/KT88, 2 x ECC82 Dimension: 37.5 cm x 40 cm x H 18 cm Net Weight: 18kg</p> <p>Cherry / Mahogany € 3.390</p>
	<p>Sinfonia Type: Dual mono Stereo Integrated Valve Amplifier Output Stage: single ended parallel ultraliner A class Output Power: 25W Inputs: 4 line, 1 tape Outputs: 1 tape, 1 subwoofer Output Impedance: 4 – 8 ohm Frequency Response: 20 – 30000 Hz Valves: 4 x 6550/KT88, 2 x ECC82, 2 x ECC83 Remote Control: IR inputs and volume Dimension: 44 cm x 42 cm x H 21 cm Net Weight: 25 kg</p> <p>Cherry / Mahogany € 5.590</p>

	<p>Sinfonia 25 Anniversary Sinfonia met Genalex Gold Lion buizen, Mundorf condensatoren en koperkleurige bovenplaat Cherry / Mahogany</p> <p style="text-align: right;">€ 6.490</p>
	<p>Performance Type: Dual mono Stereo Integrated Valve Amplifier Output Stage: parallel single ended ultralinare A class Output Power: 40 W Inputs: 4 line, 1 tape Outputs: 1 tape, loudspeakers bi-wiring Output Impedance: 4 – 8 ohm Frequency Response: 20 Hz – 30 kHz Valves: 6 x 6550/KT88 , 2 x ECC82 , 2 x ECC83 Power Consumption: 500VA max Dimension: 60cm x 48cm x H 23,5 cm. Net Weight: 50 Kg /110lb</p> <p>Cherry / Mahogany</p> <p style="text-align: right;">€ 11.490</p>
	<p>Performance 25th Anniversary Genalex Gold Lion buizen, Mundorf condensatoren, speciale eindtrafo's en koperkleurige bovenplaat Cherry / Mahogany</p> <p style="text-align: right;">€ 11.990</p>
	<p>Simply 845 Type Integrated tube amplifier Tubes 2 x 845 selected, 4 x ECC82/12AU7 selected Class Pure class A Output stage topology Single-ended Maximum power 23W Bandwidth 20Hz-50kHz, +0dB; -1dB @ 12W Inputs 4 line level Outputs 1 tape, 1 subwoofer Sizes Without packaging: 37 cm x 26cm x 57 cm (LxHxD) Weight 30,5 kg</p> <p>Cherry / Mahogany</p> <p style="text-align: right;">€ 8.890</p>
	<p>Absolute 845 SE Type: Dual mono Stereo Integrated Valve Amplifier Stadio di usita: single ended parallelo A class Output Power: 40 watt / channel Output Impedance: 4 – 8 Ohm Inputs: 5 line, 2 tape Outputs: 2 tape, loudspeakers bi-wiring Frequency Response: 20 Hz – 30 kHz Valves: 4 x 845, 6 x ECC82, 2 x ECC83 Dimension: 31,7 x 23,8 x 11 inches Net Weight: 199 lbs</p> <p>Cherry</p> <p style="text-align: right;">€ 37.990</p>

	<p>Reference Pre type: tube preamplifier, dual mono, two chassis Valves: 2 x 300B, 2 x ECC82, 4 x ECC83, 6 x 6C45P Phono Valves: 4 x 6C45P, 2 x ECC83 Class: pure class A Inputs: 4 RCA, 2 XLR, 1 tape, 2 independent phono Output: 1 RCA, 1 XLR, 1 tape (active), 1 sub woofer (active), Power-on link for REFERENCE Power Distortion: 0.1% Dimensions: 45 cm x 56 cm x H 22 cm Net Weight: 30 Kg / 66 lb</p> <p>Cherry € 18.900</p>
	<p>Reference Type: Mono Valve Amplifier Output Stage: double parallel single-ended Classe: A pura Valves: 4 x 845, 1 x ECC82, 1 x ECC83 Output Power: 80 watt Frequency Response: 20 Hz – 30 kHz Output Impedance: 4 Ohm, 8 Ohm Outputs: loudspeakers bi-wiring Inputs: 1 x RCA , 1 x XLR Dimension: 49 cm x 77.5 cm x H 28,5 cm Net Weight: 155 lbs</p> <p>Cherry € 38.000</p>

UNICO SERIES		
Amplifiers		
	<p>Unico Primo Output power: >80W Input stage: Triodi A-Class A Valve: 1 x ECC83 Frequency response: -0.1dB@10Hz / -0.5dB@100kHz THD: 0.15% @ 10W, 1kHz Inputs: 5 line RCA (1 phono optional), 1 tape RCA Output: 1 tape RCA, 1 subwoofer RCA Dimensions : 43.5 cm x 43 cm x H 9.5 cm Net weight: 14 kg / 31 lb</p>	
	Zilver	€ 1.990
	Zwart	€ 2.140
	MM/MC phono pre-pre, inclusief inbouwkosten	
	<p>Unico Nuovo Output Power: 95W RMS/ 80hm Frequency response: -0.1dB @ 10Hz, -0.5dB @ 100kHz Input stage: Pure A Class, parallel Valve stage, ECC83/12AX7 Output stage: Dynamic A Class POWER MOSFET complementary Input: 5 Line RCA (1 phono optional) Line Output: 1 tape, 1 sub (with volume control) Output Connector: 4 + 4 bi-wiring THD: 0.15% @ 10W/1kHz Size: 43.5cm x 9.5cm x 43cm Weight: 16kg</p>	
	Zilver	€ 2.290
	Zwart	€ 2.440
	MM/MC phono pre-pre, inclusief inbouwkosten	
	<p>Unico Due Output power: 100+100W RMS into 8 Ohms, 180+180W RMS into 4 Ohms, 290W+290W RMS into 2 Ohms Output stage: Dynamic Class A power BJT double complementary pair, "Super-Symmetric" configuration Biasing: Dynamic Class A Valves: 2 x ECC83 (12AX7) Inputs: 3 analogue line (RCA), 1 digital (USB), 1 tape RCA Analogue line Outputs: 1 tape (RCA), 1 stereo subwoofer (RCA), 1 DAC Dimensions: 43.5 x 43 x 13 cm (W x D x H)</p>	
	Zilver	€ 3.090
	Zwart	€ 3.290
	<p>Unico 90 Output power: 100+100 W RMS su 8Ω / 160+160 W RMS su 4Ω Frequency response: -1dB @ 12Hz e 45kHz -3 dB Input stage: Pure A class, double triode totem pole ECC83 and parallel totem pole ECC81 Output stage: Class AB thermostable, complementary Hexfet (3 pairs for channel) Input: 6 line (3 unbalanced, 2 balanced, 1 "bypass" unbalanced) Line Outputs: 1 tape, 1 sub (volume controlled) Output connectors: 4 + 4 bi-wiring Dimensions: 43.5cm x 44 cm x 18 cm Net weight: 20 kg</p>	
	Zilver	€ 4.790
	Zwart	€ 4.990
	<p>Unico 150 Output power: 150+150 W RMS at 8Ω / 220+220 W RMS at 4Ω Frequency response: -1dB @ 12Hz & 45kHz, -3 dB @ 6Hz & 80 kHz Input stage: Pure A class, double triode totem pole ECC83 Driver stage Pure A class, double triode totem pole 6H30 Output stage: Class AB thermostable, complementary Hexfet (4 pairs for channel) Input: 6 line (3 unbalanced, 2 balanced, 1 "bypass" unbalanced) Line Outputs: 1 tape, 1 sub (volume controlled) Output connectors: 4 + 4 bi-wiring THD: < 0.15% @ 1kHz, 1 W < 0.25% @ 1kHz, 10 W < 0.35% @ 1kHz, 100 W < 0.9% da 20 a 20000 Hz, 150 W Dimensions: 43.5 cm x 18 cm x 44 cm Net weight: 25 kg</p>	
	Zilver	€ 5.690
	Zwart	€ 5.890

Source					
	<p>Unico CD Uno Valvole: 1 x ECC82 Digital Inputs: 1 x USB 2.0: 44.1 – 384 kHz , DSD128, DSD256 Ready Res: 16 to 32 bits 1 x Toslink™ : 44.1 – 96 Res.: 16 to 24 bits 1 x Bluetooth™ 3.0 : 44.1, 48kHz Res: 16 bits Digital Output: 1x S/PDIF 0.5Vpp on 75 Ohms DAC: ESS Sabre ES9018K2M SNR: 125dB (0dBFS, 1kHz, 192kHz, "A" weighted) THD+N: 0.0003% (0dBFS, 1kHz, 20Hz-20kHz) Filters: 3 Digital Filters selectable by R.C. Selectable absolute Phase Dimensions: 45cm x 38cm x H 13cm Net weight: 10Kg</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Zilver</td> <td style="text-align: right;">€ 2.690</td> </tr> <tr> <td>Zwart</td> <td style="text-align: right;">€ 2.890</td> </tr> </table>	Zilver	€ 2.690	Zwart	€ 2.890
Zilver	€ 2.690				
Zwart	€ 2.890				
	<p>Unico Duo Digital Inputs: 1 x USB 2.0: 44.1 – 384 kHz , DSD128, DSD256 Ready Res: 16 to 32 bits 1 x S/PDIF: 0.5Vpp on 75 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits 1 x AES/EBU: 2Vpp on 110 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits 1 x Toslink™ : 44.1 – 96 Res.: 16 to 24 bits 1 x Bluetooth™ 3.0 : 44.1, 48kHz Res: 16 bits Digital Output: 1 x S/PDIF 0.5Vpp on 75 Ohms 1 x AES/EBU 2Vpp on 110 Ohms 1 x Toslink™ DAC: ESS Sabre ES9018K2M SNR: 128dB (0dBFS, 1kHz, 192kHz, "A" weighted) Output stage: Duple Triode, pure class A differential Totem-pole Valve model: 4 x ECC83 Output audio connectors: 2 x RCA, 2 x XLR Filters: 3 Digital Filters selectable by R.C. Selectable absolute Phase Dimension: 45cm x 38cm x 13cm Net weight: 10Kg</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Zilver</td> <td style="text-align: right;">€ 4.240</td> </tr> <tr> <td>Zwart</td> <td style="text-align: right;">€ 4.440</td> </tr> </table>	Zilver	€ 4.240	Zwart	€ 4.440
Zilver	€ 4.240				
Zwart	€ 4.440				

