





<b>VALVE SERIES</b>	
	<p><b>Simply Italy</b>                      Type: Stereo Integrated Valve Amplifier                      Valve complement: 2 x ECC82 (12AU7) 2 x EL34 (6CA7)                      Output stage: Single-ended, ultralinear, Class-A                      Output power: Approx. 12 watts per channel                      Output impedance: 6 Ohm                      Input: 4 Line , 1 USB DAC optional                      Negative feedback: 5 dB or 1.8 dB                      Dimensions: 26 cm x 35 cm x 19cm                      Net weight: 15kg</p> <p>Cherry / Black <span style="float: right;"><b>€ 2.600</b></span></p> <p>Simply Italy Incl. USB-dac (PCM 384kHz DSD-128) <span style="float: right;"><b>€ 2.900</b></span></p>
	<p><b>Triode 25</b>                      Output Stage: Push-pull, ultralinear, Class-AB                      Output Power: Approx. 45 watt per channel in Ultralinear (Pentode) configuration. Approx. 25 watt per channel Triode configuration                      Output Impedance: 6 Ohm                      Input: 4 Linea (1 Tape), 1 USB DAC                      Output: 1 Tape out, 1 Sub Out                      Negative feedback: 5 dB or 1.8 dB                      Valve complement: 2 x ECC83, 1 x ECC82, 4 x EL34                      Dimensions: 30 cm x 45 cm x 20cm                      Net weight : 20 Kg</p> <p>Cherry / Black <span style="float: right;"><b>€ 3.800</b></span></p>
	<p><b>S6 mkII</b>                      Type: Stereo Integrated Valve Amplifier                      Valves: 2 x ECC83, 6 x EL34 (Bias adjustable for each power valves)                      Output Stage: single-ended parallel, ultraliner                      Classe: pure A class                      Output Power: 30/35 Watt/channel                      Frequency Response: 20 – 50000 Hz                      Output Impedance: 6 Ohm                      Inputs: 5 line                      Outputs: 1 tape                      Dimensioni : 35 cm x 21cm x 49 cm (L x H x D)                      Net Weight: 25 kg</p> <p>Cherry / Black <span style="float: right;"><b>€ 4.490</b></span></p>
	<p><b>Preludio</b>                      Type: Stereo Integrated Valve Amplifier                      Output Stage: single ended ultraliner A class                      Output Power: 14W / channel                      Inputs: 4 line, 1 tape                      Outputs: 1 tape, 1 sub woofer                      Output Impedance: 6 ohm                      Frequency Response: 20Hz – 85kHz ( -1dB@ 7 W )                      Valves: 2 x 6550/KT88, 2 x ECC82                      Dimension: 37.5 cm x 40 cm x H 18 cm                      Net Weight: 18kg</p> <p>Cherry / Mahogany <span style="float: right;"><b>€ 3.390</b></span></p>
	<p><b>Sinfonia</b>                      Type: Dual mono Stereo Integrated Valve Amplifier                      Output Stage: single ended parallel ultraliner A class                      Output Power: 25W                      Inputs: 4 line, 1 tape                      Outputs: 1 tape, 1 subwoofer                      Output Impedance: 4 – 8 ohm                      Frequency Response: 20 – 30000 Hz                      Valves: 4 x 6550/KT88, 2 x ECC82, 2 x ECC83                      Remote Control: IR inputs and volume                      Dimension: 44 cm x 42 cm x H 21 cm                      Net Weight: 25 kg</p> <p>Cherry / Mahogany <span style="float: right;"><b>€ 5.700</b></span></p>

<b>VALVE SERIES</b>	
	<p><b>Sinfonia 25 Anniversary</b> Sinfonia met Genalex Gold Lion buizen, Mundorf condensatoren en koperkleurige bovenplaat Cherry / Mahogany</p> <p style="text-align: right;"><b>€ 6.600</b></p>
	<p><b>Performance</b> Type: Dual mono Stereo Integrated Valve Amplifier Output Stage: parallel single ended ultralinare A class Output Power: 40 W Inputs: 4 line, 1 tape Outputs: 1 tape, loudspeakers bi-wiring Output Impedance: 4 – 8 ohm Frequency Response: 20 Hz – 30 kHz Valves: 6 x 6550/KT88 , 2 x ECC82 , 2 x ECC83 Power Consumption: 500VA max Dimension: 60cm x 48cm x H 23,5 cm. Net Weight: 50 Kg /110lb Cherry / Mahogany</p> <p style="text-align: right;"><b>€ 11.490</b></p>
	<p><b>Performance 25th Anniversary</b> Genalex Gold Lion buizen, Mundorf condensatoren, speciale eindtrafo's en koperkleurige bovenplaat Cherry / Mahogany</p> <p style="text-align: right;"><b>€ 11.990</b></p>
	<p><b>Simply 845</b> Type Integrated tube amplifier Tubes 2 x 845 selected, 4 x ECC82/12AU7 selected Class Pure class A Output stage topology Single-ended Maximum power 23W Bandwidth 20Hz-50kHz, +0dB; -1dB @ 12W Inputs 4 line level Outputs 1 tape, 1 subwoofer Sizes Without packaging: 37 cm x 26cm x 57 cm (LxHxD) Weight 30,5 kg Cherry / Mahogany</p> <p style="text-align: right;"><b>€ 8.890</b></p>
	<p><b>Absolute 845 SE</b> Type: Dual mono Stereo Integrated Valve Amplifier Stadio di usita: single ended parallelo A class Output Power: 40 watt / channel Output Impedance: 4 – 8 Ohm Inputs: 5 line, 2 tape Outputs: 2 tape, loudspeakers bi-wiring Frequency Response: 20 Hz – 30 kHz Valves: 4 x 845, 6 x ECC82, 2 x ECC83 Dimension: 31,7 x 23,8 x 11 inches Net Weight: 199 lbs Cherry</p> <p style="text-align: right;"><b>€ 37.990</b></p>

<b>VALVE SERIES</b>	
	<p><b>Reference Pre</b>                      Type: tube preamplifier, dual mono, two chassis                      Valves: 2 x 300B, 2 x ECC82, 4 x ECC83, 6 x 6C45P                      Phono Valves: 4 x 6C45P, 2 x ECC83                      Class: pure class A                      Inputs: 4 RCA, 2 XLR, 1 tape, 2 independent phono                      Output: 1 RCA, 1 XLR, 1 tape ( active ), 1 sub woofer ( active ), Power-on link for REFERENCE Power                      Distortion: 0.1%                      Dimensions: 45 cm x 56 cm x H 22 cm                      Net Weight: 30 Kg / 66 lb                      Cherry</p>
<b>€ 18.900</b>	
	<p><b>Reference</b>                      Type: Mono Valve Amplifier                      Output Stage: double parallel single-ended                      Classe: A pura                      Valves: 4 x 845, 1 x ECC82, 1 x ECC83                      Output Power: 80 watt                      Frequency Response: 20 Hz – 30 kHz                      Output Impedance: 4 Ohm, 8 Ohm                      Outputs: loudspeakers bi-wiring                      Inputs: 1 x RCA , 1 x XLR                      Dimension: 49 cm x 77.5 cm x H 28,5 cm                      Net Weight: 155 lbs                      Cherry</p>
<b>€ 38.000</b>	

<b>VALVE SERIES BLACK EDITION</b>	
	<p><b>Simply Italy B.E.</b>                      Type: Stereo Integrated Valve Amplifier                      Valve complement: 2x ECC82 Gold Lion, 2x KT77 Gold Lion                      Output power: 10 watts per channel                      Input: 3 Line, 1x USB, 1x SPDIF, 1x Toslink                      Output: 1x subwoofer RCA                      Feedback: Selectable between 4 dB and 3dB                      Dimensions: 26 cm x 18 cm x 40 cm (L x H x D)                      Net weight: 15kg                      Simply Italy B.E.</p>
<b>€ 3.350</b>	
	<p><b>Triode 25 B.E.</b>                      Valve complement: 2x ECC83 Gold Lion, 4x KT77 Gold Lion (push pull)                      Output Stage: Push-pull, ultralinear, Class-AB.                      Output Power: 50 watt Pentode mode, 30 watt Triode.                      Input: 3x Line RCA, 1x USB, 1x SPDIF, 1x Toslink.                      Output: 1 subwoofer RCA (stereo), 1 line out.                      Feedback: 10dB to 12dB selectable.                      Valve complement: 2 x ECC83 Gold Lion, 1 x ECC82 Gold Lion, 4 x KT77 Gold Lion.                      Dimensions: 30 cm x 20 cm x 45 cm (L x H x D)                      Net weight : 20 Kg                      Triode 25 B.E.</p>
<b>€ 4.300</b>	
	<p><b>S6 B.E.</b>                      Type: Stereo Integrated Valve Amplifier                      Valves: 2x ECC83 Gold Lion, 6x KT77 Gold Lion (3 in parallel for each channel)                      Output Stage: single-ended parallel, ultraliner                      Classe: pure A class                      Output Power: 40Watt/channel on 60Ohm                      Frequency Response: 15 – 30000 Hz                      Output Impedance: 6 Ohm                      Inputs: 4x line RCA, 1x USB, 1x SPDIF, 1x Toslink                      Outputs: 1x subwoofer RCA (stereo)                      Dimension: 35 cm x 22 cm x 49 cm (L x H x D)                      Net Weight: 25 kg                      S6 B.E.</p>
<b>€ 5.900</b>	

<b>UNICO SERIES</b>		
<b>Amplifiers</b>		
	<p><b>Unico Primo</b>                      Output power: &gt;80W                      Input stage: Triodi A-Class A                      Valve: 1 x ECC83                      Frequency response: -0.1dB@10Hz / -0.5dB@100kHz                      THD: 0.15% @ 10W, 1kHz                      Inputs: 5 line RCA ( 1 phono optional ), 1 tape RCA                      Output: 1 tape RCA, 1 subwoofer RCA                      Dimensions : 43.5 cm x 43 cm x H 9.5 cm                      Net weight: 14 kg / 31 lb</p>	
	Zilver	<b>€ 2.150</b>
	Zwart	<b>€ 2.150</b>
	MM/MC phono pre-pre, inclusief inbouwkosten	
	<p><b>Unico Nuovo</b>                      Output Power: 95W RMS/ 80hm                      Frequency response: -0.1dB @ 10Hz, -0.5dB @ 100kHz                      Input stage: Pure A Class, parallel Valve stage, ECC83/12AX7                      Output stage: Dynamic A Class POWER MOSFET complementary                      Input: 5 Line RCA (1 phono optional)                      Line Output: 1 tape, 1 sub (with volume control)                      Output Connector: 4 + 4 bi-wiring                      THD: 0.15% @ 10W/1kHz                      Size: 43.5cm x 9.5cm x 43cm                      Weight: 16kg</p>	
	Zilver	<b>€ 2.600</b>
	Zwart	<b>€ 2.600</b>
	MM/MC phono pre-pre, inclusief inbouwkosten	
	<p><b>Unico Due</b>                      Output power: 100+100W RMS into 8 Ohms, 180+180W RMS into 4 Ohms, 290W+290W RMS into 2 Ohms                      Output stage: Dynamic Class A power BJT double complementary pair, "Super-Symmetric" configuration                      Biasing: Dynamic Class A                      Valves: 2 x ECC83 (12AX7)                      Inputs: 3 analogue line (RCA), 1 digital (USB), 1 tape RCA                      Analogue line Outputs: 1 tape (RCA), 1 stereo subwoofer (RCA), 1 DAC                      Dimensions: 43.5 x 43 x 13 cm (W x D x H)</p>	
	Zilver	<b>€ 3.200</b>
	Zwart	<b>€ 3.200</b>
	<p><b>Unico 90</b>                      Output power: 100+100 W RMS su 8Ω / 160+160 W RMS su 4Ω                      Frequency response: -1dB @ 12Hz e 45kHz -3 dB                      Input stage: Pure A class, double triode totem pole ECC83 and parallel totem pole ECC81                      Output stage: Class AB thermostable, complementary Hexfet (3 pairs for channel)                      Input: 6 line (3 unbalanced, 2 balanced, 1 "bypass" unbalanced)                      Line Outputs: 1 tape, 1 sub (volume controlled)                      Output connectors: 4 + 4 bi-wiring                      Dimensions: 43.5cm x 44 cm x 18 cm                      Net weight: 20 kg</p>	
	Zilver	<b>€ 4.990</b>
	Zwart	<b>€ 4.990</b>
	<p><b>Unico 150</b>                      Output power: 150+150 W RMS at 8Ω / 220+220 W RMS at 4Ω                      Frequency response: -1dB @ 12Hz &amp; 45kHz, -3 dB @ 6Hz &amp; 80 kHz                      Input stage: Pure A class, double triode totem pole ECC83                      Driver stage Pure A class, double triode totem pole 6H30                      Output stage: Class AB thermostable, complementary Hexfet (4 pairs for channel)                      Input: 6 line (3 unbalanced, 2 balanced, 1 "bypass" unbalanced)                      Line Outputs: 1 tape, 1 sub (volume controlled)                      Output connectors: 4 + 4 bi-wiring                      THD: &lt; 0.15% @ 1kHz, 1 W &lt; 0.25% @ 1kHz, 10 W &lt; 0.35% @ 1kHz, 100 W &lt; 0.9% da 20 a 20000 Hz, 150 W                      Dimensions: 43.5 cm x 18 cm x 44 cm                      Net weight: 25 kg</p>	
	Zilver	<b>€ 5.890</b>
	Zwart	<b>€ 5.890</b>

<b>Source</b>		
	<p><b>Unico CD Uno</b>                      Valvole: 1 x ECC82                      Digital Inputs:                      1 x USB 2.0: 44.1 – 384 kHz , DSD128, DSD256 Ready Res: 16 to 32 bits                      1 x Toslink™ : 44.1 – 96 Res.: 16 to 24 bits                      1 x Bluetooth™ 3.0 : 44.1, 48kHz Res: 16 bits                      Digital Output:                      1x S/PDIF 0.5Vpp on 75 Ohms                      DAC: ESS Sabre ES9018K2M                      SNR: 125dB (0dBFS, 1kHz, 192kHz, "A" weighted )                      THD+N: 0.0003% (0dBFS, 1kHz, 20Hz-20kHz)                      Filters: 3 Digital Filters selectable by R.C.                      Selectable absolute Phase                      Dimensions: 45cm x 38cm x H 13cm                      Net weight: 10Kg</p>	
	<b>Zilver</b>	<b>€ 2.990</b>
	<b>Zwart</b>	<b>€ 2.990</b>
	<p><b>Unico CD Duo</b>                      Digital Inputs: 1 x USB 2.0: 44.1 – 384 kHz , DSD128, DSD256 Ready Res: 16 to 32 bits                      1 x S/PDIF: 0.5Vpp on 75 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits                      1 x AES/EBU: 2Vpp on 110 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits                      1 x Toslink™ : 44.1 – 96 Res.: 16 to 24 bits                      1 x Bluetooth™ 3.0 : 44.1, 48kHz Res: 16 bits                      Digital Output: 1 x S/PDIF 0.5Vpp on 75 Ohms                      1 x AES/EBU 2Vpp on 110 Ohms                      1 x Toslink™                      DAC: ESS Sabre ES9018K2M SNR: 128dB (0dBFS, 1kHz, 192kHz, "A" weighted )                      Output stage: Duple Triode, pure class A differential Totem-pole                      Valve model: 4 x ECC83                      Output audio connectors: 2 x RCA, 2 x XLR                      Filters: 3 Digital Filters selectable by R.C.                      Selectable absolute Phase                      Dimension: 45cm x 38cm x 13cm                      Net weight: 10Kg</p>	
	<b>Zilver</b>	<b>€ 4.250</b>
	<b>Zwart</b>	<b>€ 4.250</b>

<b>Phonoamplifier</b>				
	<p><b>Uphono+</b> Analogic moving magnet input (MM) /High output moving coil (MC) Fixed analogue output &amp; Variable analogue output. Headphones (16-600Ω): ¼ inch (6.35mm) stereo jack socket Type B USB Digital port for pc connection (up to 24 bit / 96 kHz) Digital Output: Digital Optical, Digital Coaxial Input impedance: MM 47kΩ + 100/200/320 / 420pF MC 20/50/100/150/250/500 / 1kΩ + 1nF RIAA curve accuracy +/- 0.3dB from 20Hz to 30kHz IEC anti-rumble filter -3dB at 20Hz and 6dB/octave Line output impedance Fixed 824Ω Variable 824Ω Headphone stage Output level 2.18VRMS Max THD+N 0.07% (1kHz /32Ω) USB A/D Resolution 16/24 bit Sample rates 8, 16, 32, 44.1, 48, 88.2, 96kHz Coaxial digital output 0.5Vp-p a 75Ω / 96kHz max. Dimensions (H x W x D) 82.5 x 216mm x 251mm (3.25 x 8.5 x 9.9 inches) including feet, connectors and knobs Weight 2.6Kg (lbs)</p>			
	<table border="1" style="width: 100%;"> <tr> <td>Zilver</td> <td style="text-align: right;"><b>€ 1.040</b></td> </tr> <tr> <td>Zwart</td> <td style="text-align: right;"><b>€ 1.040</b></td> </tr> </table>	Zilver	<b>€ 1.040</b>	Zwart
Zilver	<b>€ 1.040</b>			
Zwart	<b>€ 1.040</b>			
	<p><b>Simply Phono</b> Type : Stereo Phono Valve preamplifier Classe: pure A class RIAA : passiva +/- 0.2 dB ( 20 Hz / 20 KHz ) Output: 1 x line Inputs: 1 x MM, 1 x MC Input Impedance: 47 Kohm – 100 – 50 – 22 ohm / 100 pF (modifiable) Valves: 4 x ECC83 / 12AX7 Dimension: 140 x 290 x h 105 ( mm ) Net Weight: 3 Kg (including power supply)</p>			
	<table border="1" style="width: 100%;"> <tr> <td>Simply Phono exclusief PSU Simply Phono</td> <td style="text-align: right;"><b>€ 1.550</b></td> </tr> <tr> <td>Simply Phono inclusief PSU Simply Phono</td> <td style="text-align: right;"><b>€ 2.270</b></td> </tr> </table>	Simply Phono exclusief PSU Simply Phono	<b>€ 1.550</b>	Simply Phono inclusief PSU Simply Phono
Simply Phono exclusief PSU Simply Phono	<b>€ 1.550</b>			
Simply Phono inclusief PSU Simply Phono	<b>€ 2.270</b>			
	<p><b>Phono One</b> Type: Stereo Phono Valve preamplifier Class: pure A RIAA : passive +/- 0.1 dB (20 Hz / 20 KHz) Outputs: 1 x line Inputs: 1 x MM, 1 x MC Input Impedance: 47 Kohm – 100 – 50 – 22 ohm / 100 – 200 – 320 – 420 pF ( modifiable ) Valves: 5 x ECC83 / 12AX7 Dimension: 37.3 x 5.84 x h 24.63 cm. Net Weight: 3.6 Kg circa (including power supply)</p>			
	<table border="1" style="width: 100%;"> <tr> <td>Cherry / Mahogany</td> <td style="text-align: right;"><b>€ 2.850</b></td> </tr> </table>	Cherry / Mahogany	<b>€ 2.850</b>	
Cherry / Mahogany	<b>€ 2.850</b>			
<b>Hoofdtelefoon buizenversterker</b>				
	<p><b>SH</b> Frequency Response: -0.1 dB @ 10Hz / 3-dB @ 50 kHz (output "Low sensibility", 33 ohm load) Input stage: Pure Class A, ECC83/12AX7 Output stage: Class A, 2 EL84 triode connected Inputs: 1 line RCA, 1 USB Outputs : 2 (parallel connected) Dimension: 22,5 cm x 12,6 cm x 32,2 cm Weight: 6 kg</p>			
	<table border="1" style="width: 100%;"> <tr> <td>Cherry / Black</td> <td style="text-align: right;"><b>€ 1.790</b></td> </tr> </table>	Cherry / Black	<b>€ 1.790</b>	
Cherry / Black	<b>€ 1.790</b>			