

---

**VALVE SERIES BLACK EDITION**

---



**Simply Italy B.E.**

Type: Stereo Integrated Valve Amplifier  
Valve complement: 2x ECC82 Gold Lion, 2x KT77 Gold Lion  
Output power: 10 watts per channel  
Input: 3 Line, 1x USB, 1x SPDIF, 1x Toslink  
Output: 1x subwoofer RCA  
Feedback: Selectable between 4 dB and 3dB  
Dimensions: 26 cm x 18 cm x 40 cm (L x H x D)  
Net weight: 15kg

**€ 3.600**



**Triode 25 B.E.**

Valve complement: 2x ECC83 Gold Lion, 4x KT77 Gold Lion (push pull)  
Output Stage: Push-pull, ultralinear, Class-AB.  
Output Power: 50 watt Pentode mode, 30 watt Triode.  
Input: 3x Line RCA, 1x USB, 1x SPDIF, 1x Toslink.  
Output: 1 subwoofer RCA (stereo), 1 line out.  
Feedback: 10dB to 12dB selectable.  
Valve complement: 2 x ECC83 Gold Lion, 1 x ECC82 Gold Lion, 4 x KT77 Gold Lion.  
Dimensions: 30 cm x 20 cm x 45 cm (L x H x D)  
Net weight : 20 Kg

**€ 4.500**



**S6 B.E.**

Type: Stereo Integrated Valve Amplifier  
Valves: 2x ECC83 Gold Lion, 6x KT77 Gold Lion (3 in parallel for each channel)  
Output Stage: single-ended parallel, ultraliner  
Classe: pure A class  
Output Power: 40Watt/channel on 60hm  
Frequency Response: 15 – 30000 Hz  
Output Impedance: 6 Ohm  
Inputs: 4x line RCA, 1x USB, 1x SPDIF, 1x Toslink  
Outputs: 1x subwoofer RCA (stereo)  
Dimensioni : 35 cm x 22 cm x 49 cm (L x H x D)  
Net Weight: 25 kg

**€ 6.000**

**VALVE SERIES**



**Sinfonia 25 Anniversary**

Type: Dual mono Stereo Integrated Valve Amplifier Output Stage: single ended parallel ultraliner A class  
 Output Power: 25W Inputs: 4 line, 1 tape Outputs: 1 tape, 1 subwoofer Output Impedance: 4 – 8 ohm  
 Frequency Response: 20 – 30000 Hz  
 Valves: 4 x 6550/KT88, 2 x ECC82, 2 x ECC83  
 Remote Control: IR inputs and volume  
 Dimension: 44 cm x 42 cm x H 21 cm  
 Net Weight: 25 kg  
 Cherry / Mahogany

**€ 6.700**



**Performance 25th Anniversary**

Type: Dual mono Stereo Integrated Valve Amplifier Output Stage: parallel single ended ultralinare A class  
 Output Power: 40 W Inputs: 4 line, 1 tape Outputs: 1 tape, loudspeakers bi-wiring Output Impedance: 4 – 8 ohm  
 Frequency Response: 20 Hz – 30 kHz  
 Valves: 6 x 6550/KT88 , 2 x ECC82 , 2 x ECC83  
 Power Consumption: 500VA max  
 Dimension: 60cm x 48cm x H 23,5 cm.  
 Net Weight: 50 Kg  
 Cherry / Mahogany

**€ 12.900**



**Simply 845**

Type Integrated tube amplifier  
 Tubes 2 x 845 selected, 4 x ECC82/12AU7 selected  
 Class Pure class A  
 Output stage topology Single-ended  
 Maximum power 23W  
 Bandwidth 20Hz-50kHz, +0dB; -1dB @ 12W  
 Inputs 4 line level  
 Outputs 1 tape, 1 subwoofer  
 Sizes Without packaging: 37 cm x 26cm x 57 cm (LxHxD)  
 Weight 30,5 kg  
 Cherry / Mahogany

**€ 9.500**



**Absolute 845 SE**

Type: Dual mono Stereo Integrated Valve Amplifier  
 Stadio di usita: single ended parallelo A class  
 Output Power: 40 watt / channel  
 Output Impedance: 4 – 8 Ohm  
 Inputs: 5 line, 2 tape  
 Outputs: 2 tape, loudspeakers bi-wiring  
 Frequency Response: 20 Hz – 30 kHz  
 Valves: 4 x 845, 6 x ECC82, 2 x ECC83  
 Dimension: 31,7 x 23,8 x 11 inches  
 Net Weight: 199 lbs  
 Cherry

**€ 38.000**



**Reference Pre**

ype: tube preamplifier, dual mono, two chassis  
 Valves: 2 x 300B, 2 x ECC82, 4 x ECC83, 6 x 6C45P  
 Phono Valves: 4 x 6C45P, 2 x ECC83  
 Class: pure class A  
 Inputs: 4 RCA, 2 XLR, 1 tape, 2 independent phono  
 Output: 1 RCA, 1 XLR, 1 tape ( active ), 1 sub woofer ( active ), Power-on link for REFERENCE Power  
 Distortion: 0.1%  
 Dimensions: 45 cm x 56 cm x H 22 cm  
 Net Weight: 30 Kg / 66 lb  
 Cherry

**€ 19.500**



**Reference Power**

Type: Mono Valve Amplifier  
 Output Stage: double parallel single-ended  
 Classe: A pura  
 Valves: 4 x 845, 1 x ECC82, 1 x ECC83  
 Output Power: 80 watt  
 Frequency Response: 20 Hz – 30 kHz  
 Output Impedance: 4 Ohm, 8 Ohm  
 Outputs: loudspeakers bi-wiring  
 Inputs: 1 x RCA , 1 x XLR  
 Dimension: 49 cm x 77.5 cm x H 28,5 cm  
 Net Weight: 155 lbs  
 Cherry

**€ 38.000**

---

**UNICO SERIES**


---

**Amplifiers**


---

**Unico Primo**

Output power: >80W  
 Input stage: Triodi A-Class A  
 Valve: 1 x ECC83  
 Frequency response: -0.1dB@10Hz / -0.5dB@100kHz  
 THD: 0.15% @ 10W, 1kHz  
 Inputs: 5 line RCA ( 1 phono optional ), 1 tape RCA  
 Output: 1 tape RCA, 1 subwoofer RCA  
 Dimensions : 43.5 cm x 43 cm x H 9.5 cm  
 Net weight: 14 kg / 31 lb  
 Silver or black

€ 2.450

MM/MC phono pre-pre, inclusief inbouwkosten

€ 200

**Unico Nuovo**

Output Power: 95W RMS/ 80hm  
 Frequency response: -0.1dB @ 10Hz, -0.5dB @ 100kHz  
 Input stage: Pure A Class, parallel Valve stage, ECC83/12AX7  
 Output stage: Dynamic A Class POWER MOSFET complementary  
 Input: 5 Line RCA (1 phono optional)  
 Line Output: 1 tape, 1 sub (with volume control)  
 Output Connector: 4 + 4 bi-wiring  
 THD: 0.15% @ 10W/1kHz  
 Size: 43.5cm x 9.5cm x 43cm  
 Weight: 16kg  
 Silver or black

€ 2.900

MM/MC phono pre-pre, inclusief inbouwkosten

€ 200

**Unico Due**

Output power: 100+100W RMS into 8 Ohms, 180+180W RMS into 4 Ohms, 290W+290W RMS into 2 Ohms  
 Output stage: Dynamic Class A power BJT double complementary pair, "Super-Symmetric" configuration  
 Biasing: Dynamic Class A  
 Valves: 2 x ECC83 (12AX7)  
 Inputs: 3 analogue line (RCA), 1 digital (USB), 1 tape RCA  
 Analogue line Outputs: 1 tape (RCA), 1 stereo subwoofer (RCA), 1 DAC  
 Dimensions: 43.5 x 43 x 13 cm (W x D x H)  
 Silver or black

€ 3.500

**Unico 90**

Output power: 100+100 W RMS su 8Ω / 160+160 W RMS su 4Ω  
 Frequency response: -1dB @ 12Hz e 45kHz -3 dB  
 Input stage: Pure A class, double triode totem pole ECC83 and parallel totem pole ECC81  
 Output stage: Class AB thermostable, complementary Hexfet (3 pairs for channel)  
 Input: 6 line (3 unbalanced, 2 balanced, 1 "bypass" unbalanced)  
 Line Outputs: 1 tape, 1 sub (volume controlled)  
 Output connectors: 4 + 4 bi-wiring  
 Dimensions: 43.5cm x 44 cm x 18 cm  
 Net weight: 20 kg  
 Silver or black

€ 5.200

**Unico 150**

Output power: 150+150 W RMS at 8Ω / 220+220 W RMS at 4Ω  
 Frequency response: -1dB @ 12Hz & 45kHz, -3 dB @ 6Hz & 80 kHz  
 Input stage: Pure A class, double triode totem pole ECC83  
 Driver stage Pure A class, double triode totem pole 6H30  
 Output stage: Class AB thermostable, complementary Hexfet (4 pairs for channel)  
 Input: 6 line (3 unbalanced, 2 balanced, 1 "bypass" unbalanced)  
 Line Outputs: 1 tape, 1 sub (volume controlled)  
 Output connectors: 4 + 4 bi-wiring  
 Dimensions: 43.5 cm x 18 cm x 44 cm  
 Net weight: 25 kg  
 Silver or black

€ 6.250

---

**UNICO SERIES**

---

**Source**

---



**Unico CD Uno**

Valvole: 1 x ECC82  
 Digital Inputs:  
 1 x USB 2.0: 44.1 – 384 kHz , DSD128, DSD256 Ready Res: 16 to 32 bits  
 1 x Toslink™ : 44.1 – 96 Res.: 16 to 24 bits  
 1 x Bluetooth™ 3.0 : 44.1, 48kHz Res: 16 bits  
 Digital Output:  
 1x S/PDIF 0.5Vpp on 75 Ohms  
 DAC: ESS Sabre ES9018K2M  
 SNR: 125dB (0dBFS, 1kHz, 192kHz, "A" weighted )  
 Filters: 3 Digital Filters selectable by R.C.  
 Selectable absolute Phase  
 Dimensions: 45cm x 38cm x H 13cm  
 Net weight: 10Kg  
 Silver or black

**€ 3.200**



**Unico Duo**

Digital Inputs: 1 x USB 2.0: 44.1 – 384 kHz , DSD128, DSD256 Ready Res: 16 to 32 bits  
 1 x S/PDIF: 0.5Vpp on 75 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits  
 1 x AES/EBU: 2Vpp on 110 Ohms, 44.1 -192 kHz, DSD64 (DoP) Res: 16 to 24 bits  
 1 x Toslink™ : 44.1 – 96 Res.: 16 to 24 bits  
 1 x Bluetooth™ 3.0 : 44.1, 48kHz Res: 16 bits  
 Digital Output: 1 x S/PDIF 0.5Vpp on 75 Ohms  
 1 x AES/EBU 2Vpp on 110 Ohms  
 1 x Toslink™  
 DAC: ESS Sabre ES9018K2M SNR: 128dB (0dBFS, 1kHz, 192kHz, "A" weighted )  
 Output stage: Duple Triode, pure class A differential Totem-pole  
 Valve model: 4 x ECC83  
 Output audio connectors: 2 x RCA, 2 x XLR  
 Filters: 3 Digital Filters selectable by R.C.  
 Selectable absolute Phase  
 Dimension: 45cm x 38cm x 13cm  
 Net weight: 10Kg  
 Silver or black

**€ 4.400**

---

**Phono amplifier**

---



**Simply Phono**

Type : Stereo Phono Valve preamplifier  
 Classe: pure A class  
 RIAA : passiva +/- 0.2 dB ( 20 Hz / 20 KHz )  
 Output: 1 x line  
 Inputs: 1 x MM, 1 x MC  
 Input Impedance: 47 Kohm – 100 – 50 – 22 ohm / 100 pF (modifiable)  
 Valves: 4 x ECC83 / 12AX7  
 Dimension: 140 x 290 x h 105 ( mm )  
 Net Weight: 3 Kg (including power supply)  
 Cherry / Mahogany  
 Simply Phono excluding PSU Simply Phono  
 Simply Phono including PSU Simply Phono

**€ 1.750**

**€ 2.540**



**Phono One**

Type: Stereo Phono Valve preamplifier  
 Class: pure A  
 RIAA : passive +/- 0.1 dB (20 Hz / 20 KHz)  
 Outputs: 1 x line  
 Inputs: 1 x MM, 1 x MC  
 Input Impedance: 47 Kohm – 100 – 50 – 22 ohm / 100 – 200 – 320 – 420 pF ( modifiable )  
 Valves: 5 x ECC83 / 12AX7  
 Dimension: 37.3 x 5.84 x h 24.63 cm.  
 Net Weight: 3.6 Kg circa (including power supply)  
 Cherry / Mahogany

**€ 3.100**